

## WebiSmarts System

### ROTEM RadMon Monitor DPU Display Unit (w/o detectors) CAT BAK-0336

#### Radiation Detection Division

The DPU-3 Remote Display Unit is capable of simultaneously displaying up to four detectors from any location in the Site. Setup is performed using our RMVC software which is freely available off our website.

The DPU-3 is the latest addition to the renowned WebiSmarts Area and Stack Monitoring System. Combining the same respected reliability which has made MediSmarts a world leader, with the latest state-of-the-art technology, the DPU-3 brings the 21st Century into your laboratory.

Powered via POE



## Features

- Wall Mounted or Tabletop, IP-65 high impact plastic casing
- Large, easy to read, TFT display panel
- Displays user selectable Units of Measurement and Detector Name
- Ergonomically designed to function using only 4 push-buttons which activate multilingual menus
- Background color reflects radiation levels against threshold settings
- Audio Alarm upon over threshold or detector failure
- User selectable threshold are set according to the original settings
- Automatic internal diagnostics

## Functions

- Provides Ethernet, POE connectivity
- The wide screen TFT color Display is configurable to show any of the parameters
- The Display can be setup to show up to 4 displays simultaneously

## DPU-3 Remote Display Unit

Includes:

DPU-3 Meter

Wall Bracket

4 X Shoulder Screws



### Casing:

Material: High Impact Plastic (ABS-PC) with aluminum rear cover

Dimensions: L x W x H: 230 x 76 x 252 mm ( 9" x 3" x 10")

Weight: 1.7 Kg (3.75 lb's)

Environmental: Weather proof IP-65, CE Certified

### Electronics:

Display: 7 inch HD Color Display

CPU Mainboard: ARM Cortex®-A7 core i.MX 6UltraLite (NXP)

### Power Source:

POE through Ethernet cable only

### Communication:

RJ-45: Ethernet Cable

ROTEM INDUSTRIES reserves the right to change specifications without advance notice